

FLUIDX ROTARY VANE VACUUM PUMP




The FluidX W2V20 rotary vane vacuum pump features a rugged, two-stage, air-cooled design and is capable of pumping speeds of 7 cfm and producing an ultimate vacuum of 10^{-3} Torr. Lightweight, quiet, and compact, the W2V20 features an anti-suckback and gas ballast valve, quick disconnect ISO/KF fittings, and is ideal for a variety of applications.

BENEFITS

- Well ventilated, cool running pumps minimize oil backstreaming and thermal degradation
- Positive oil feed system enables optimal pump lubrication
- Rugged, well-known design makes pump easy to maintain
- Low operating costs

APPLICATIONS

- Vacuum Degassing
- Cylinder Filling
- Sampling Applications
- AC & Refrigeration Evacuation
- Vacuum Ovens & Furnaces
- Sputter & Deposition Systems
- Freeze Dryers
- Electron Microscopes
- Backing Turbo Pumps



W2V20 SPECIFICATIONS

COMPONENT	DESCRIPTION
Pumping Speed @ 60 Hz	200 l/m, 7 cfm, 12 m ³ /hr
Pumping Speed @ 50 Hz	166 l/m, 5.8 cfm, 10 m ³ /hr
Ultimate Pressure (Gas Ballast Open)	5×10^{-2} Torr
Ultimate Pressure (Gas Ballast Closed)	1×10^{-3} Torr
Standard Motor, CE Marked	115V, 1 HP, 60 Hz, On/Off Switch
Power Connection	6 ft (2 m) 3 conductor cord
Motor Speed @ 60 Hz	1700 rpm
Oil Capacity	500 cc (.53 quart)
Weight Net	50 lbs, shipping 54 lbs
Intake/Exhaust Type/Diameter	NW 25 (26 mm) O.D. tube
Ambient Operating Temperature	70° to 40° C (45° to 104° F)
Overall Dimensions	17.08" x 5.91" x 9.88" (LWH)

